
Uncontrolled document as of May 10, 2010. Refer to website for up to date specifications.









- Lockable compartment for controlled substances
- Adjustable tray dividers allow for easy customization
- Sharps storage bracket included
- Top lid opens up to 180° for on-the-field anti-roll stability when open
- O-ring seal for dust and water resistant seal (IP66)
- Easy open Double Throw latches
- Open cell core with solid wall design strong, light weight
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handles
- Stainless steel hardware and padlock protectors
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

(Tray system not covered by lifetime warranty)

- Each tray has an overall internal dimension of: 17" x 7.65" x 1.36" (43.18 x 19.43 x 3.45cm) LxWxD
- Also available with without EMS Organizer and Dividers

#### 1460EMS Case Configurations

Cat. #	Description
1460EMS	1460EMS Case





# 1460EMS Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
20.85" x 12.73" x 12.75" (52.9 x 32.3 x 32.4 cm)	18.54" x 9.92" x 10.92" (47.1 x 25	18.54" x 9.92" x 10.92" (47.1 x 25.2 x 27.7 cm)	
Lid Depth	Bottom Depth	Total Depth	
4.91" (12.5 cm)	6.01" (15.3 cm)	10.92" (27.7 cm)	
Weight with foam	Weight without foam	Buoyancy Max.	
18.2 lbs. (8.26 kg)	lbs. (0 kg)		

## Range Temperature

-40 / 210° F (-40 / 99° C)

#### **1460EMS Case Certificates**

• IP66

## 1460EMS Case Accessories

Cat. #	Description	Sug. Retail
1463	Replacement O-ring	US\$5.50