

LIGHTS

2720

LED Headlight

NEW



2720 LED Headlight

- Gesture Activation Control
- Variable Light Output
- Dual Red LED Night Vision

Gloved hands, wet hands or oily hands are not an issue when using the 2720 with Gesture Activation Control technology. Turn on the light with a wave of a hand. Additional features include: Low level red light that preserves night vision, for nighttime applications. Signaling red (S.O.S) beacon light. Optical 4x magnification allows for a wide or penetrating beam., Including a variable light output from 100%-10%.






Body Material: ABS
Minimum Pack 0 ea.

2720 LED Headlight Specifications

2720 LED Headlight Configurations

Cat. #	Description
--------	-------------

	High	Low
LIGHT SOURCE	LED	LED (Low)
BATTERIES	3 AAA Alkaline (Included)	
CHARGE TIME		
VOLTAGE	4.5	
LENGTH	2.48" (6.3 cm)	
WEIGHT w/ BATTERIES	3.8 oz. (0.11 kg)	
WEIGHT w/o BATTERIES	2.6 oz. (0.07 kg)	

	FL1 STANDARD	High	Low
LIGHT OUTPUT		80 LUMENS	5 LUMENS
RUNTIME (hours/min)		8h	175h
BEAM DISTANCE (meters)		56m	15m
PEAK BEAM INTENSITY (candela)		790cd	60cd
WATER RESISTANT		IPX4	IPX4

Pelican Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
 e-mail: sales@pelican.com • www.pelican.com