

Uncontrolled document as of November 3, 2009. Refer to website for up to date specifications.

# CASES 1400 Case



## 1400 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Stainless steel padlock protectors
- Comfortable rubber over-molded handle
- Stainless steel hardware
- Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence

## 1400 Case Configurations

Cat. #	Description
1400	1400 Case
1400NF	1400 Case (No foam)



Black



Silver



Orange



Yellow



OD Green\*



Desert Tan

\*OD Green available upon request

## 1400 Case Specifications

<b>Exterior Dimensions (L x W x D)</b>		<b>Interior Dimensions (L x W x D)</b>	
13.37" x 11.62" x 6.00" (33.9 x 29.5 x 15.2 cm)		11.81" x 8.87" x 5.18" (30 x 22.5 x 13.2 cm)	
<b>Lid Depth</b>	<b>Bottom Depth</b>	<b>Total Depth</b>	
1.18" (3 cm)	4.00" (10.2 cm)	5.18" (13.2 cm)	
<b>Weight with foam</b>	<b>Weight without foam</b>	<b>Buoyancy Max.</b>	
4.41 lbs. (2 kg)	3.97 lbs. (1.8 kg)	20.06 lbs. (9.1 kg)	
<b>Range Temperature</b>			
-40 / 210° F (-40 / 99° C)			

Personalized Nameplate Available

## 1400 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

## 1400 Case Accessories

Cat. #	Description	Sug. Retail
1400IP	Instapak Quick® RT	US\$40.95
1400PF	Special Application Panel Frame	US\$21.95
1401	3 pc. Replacement Foam Set	US\$36.25
1403	Replacement O-ring	US\$4.60

### Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)