

Uncontrolled document as of May 10, 2010. Refer to website for up to date specifications.

CASES 1460 Case



1460 Case

- Top lid opens up to 180° for on-the-field anti-roll stability when open
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handles
- Stainless steel hardware and padlock protectors
- Pick N Pluck™ foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- [Also available with EMS Organizer and Dividers](#)
- Watertight, crushproof, and dust proof

1460 Case Configurations

Cat. #	Description
1460	1460 Case
1460NF	1460 Case (No foam)
1460AALG	1460 Case (with custom foam for 9430/9435)



Black



OD Green*



Desert Tan

*OD Green available upon request

1460 Case Specifications

Exterior Dimensions (L x W x D)		Interior Dimensions (L x W x D)	
20.85" x 12.73" x 12.75" (52.9 x 32.3 x 32.4 cm)		18.54" x 9.92" x 10.92" (47.1 x 25.2 x 27.7 cm)	
Lid Depth	Bottom Depth	Total Depth	
4.91" (12.5 cm)	6.01" (15.3 cm)	10.92" (27.7 cm)	
Weight with foam	Weight without foam	Buoyancy Max.	
12.48 lbs. (5.66 kg)	8.75 lbs. (3.97 kg)	82 lbs. (37.19 kg)	
Range Temperature			
-40 / 210° F (-40 / 99° C)			

1460 Case Certificates

- IP67 (1 meter submersion for 30 minutes)

1460 Case Accessories

Cat. #	Description	Sug. Retail
1461	Replacement Foam Set	US\$99.95
1463	Replacement O-ring	US\$5.50

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com