

Uncontrolled document as of November 3, 2009. Refer to website for up to date specifications.

CASES 1550 Case



1550 Case

- **Watertight, crushproof, and dust proof**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- 2 level Pick N Pluck™ with convoluted lid foam
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence

1550 Case Configurations

Cat. #	Description
1550	1550 Case
1550NF	1550 Case (No foam)
1554	1550 Case with Padded Dividers



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1550 Case Specifications

Exterior Dimensions (L x W x D) 20.62" x 16.87" x 8.12" (52.4 x 42.8 x 20.6 cm)	Interior Dimensions (L x W x D) 18.43" x 14.00" x 7.62" (46.8 x 35.5 x 19.3 cm)	
Lid Depth 1.75" (4.4 cm)	Bottom Depth 5.87" (14.9 cm)	Total Depth 7.62" (19.3 cm)
Weight with foam 11.9 lbs. (5.4 kg)	Weight without foam 10.58 lbs. (4.8 kg)	Buoyancy Max. 69.89 lbs. (31.7 kg)
Range Temperature -40 / 210° F (-40 / 99° C)		

Personalized Nameplate Available

1550 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1550 Case Accessories

Cat. #	Description	Sug. Retail
1550IP	Instapak Quick® RT	US\$67.95
1550PF	Special Application Panel Frame	US\$22.95
1551	4 pc. Replacement Foam Set	US\$80.95
1552	Pick N Pluck™ Sections Only (set of 2)	US\$63.95
1553	Replacement O-ring	US\$5.20
1555	Padded Divider Set Only	US\$151.95

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311

