

Uncontrolled document as of November 3, 2009. Refer to website for up to date specifications.

CASES
1730
Transport Case



1730 Transport Case



- **Extra deep stackable cleats**
- Easy open Double Throw latches
- Open cell core with solid wall design - strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Fold down handles
- Strong polyurethane wheels with stainless steel bearings
- Stainless steel hardware and padlock protectors
- 5-piece foam set
- [Personalized nameplate service available](#)
- Lifetime Guarantee of Excellence
- **Watertight, crushproof, and dust proof**
- **The following custom features require a 100 pc. minimum order**
- Optional Humidity gauge changes color above 40%
- Optional Manual Pressure Equalization Valve

1730 Transport Case Configurations

Cat. #	Description
1730	1730 Transport Case
1730NF	1730 Transport Case (No foam)



Black



OD Green*



Desert Tan

*OD Green available upon request

1730 Transport Case Specifications

Exterior Dimensions (L x W x D)	Interior Dimensions (L x W x D)	
37.50" x 27.13" x 14.37" (95.2 x 68.9 x 36.5 cm)	34.00" x 24.00" x 12.50" (86.3 x 60.9 x 31.7 cm)	
Lid Depth	Bottom Depth	Total Depth
2.50" (6.3 cm)	10.00" (25.4 cm)	12.50" (31.7 cm)
Weight with foam	Weight without foam	Buoyancy Max.
38 lbs. (17.24 kg)	30 lbs. (13.61 kg)	416 lbs. (188.69 kg)
Range Temperature	No. of Wheels	
-40 / 210° F (-40 / 99° C)	2	

Personalized Nameplate Available

1730 Transport Case Certificates

- IP67 (1 meter submersion for 30 minutes)

1730 Transport Case Accessories

Cat. #	Description	Sug. Retail
1731	5 pc. Replacement Foam Set	US\$197.95
1733	Replacement O-ring	US\$9.35

Pelican™ Products, Inc.

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311
e-mail: sales@pelican.com • www.pelican.com