

**CASES** **iM2975**  
Pelican Storm Case



**iM2975 Pelican Storm Case (Transport)**

- Five Press & Pull Latches
- Three Double-layered, Soft-grip Handles
- Two Padlockable Hasps
- In-line Wheels
- Telescoping Handle
- Vortex® Valve
- Flush Powerful Hinges
- Lightweight Strong HPX® Resin
- Watertight
- Guaranteed For Life

**iM2975 Pelican Storm Case (Transport) Configurations**

Cat. #	Description
<b>iM2975-X0001</b>	<b>iM2975 Pelican Storm Case (Transport)</b>
<b>iM2975-X0000</b>	<b>iM2975 Storm Case (No foam)</b>
<b>iM2975-X0002</b>	<b>iM2975 Storm Case with Padded Dividers</b>



Black



OD Green

**iM2975 Pelican Storm Case (Transport) Specifications**

<b>Exterior Dimensions (L x W x D)</b>		<b>Interior Dimensions (L x W x D)</b>	
31.30" x 20.40" x 15.50" (79.5 x 51.8 x 39.4 cm)		29.00" x 18.00" x 13.80" (73.6 x 45.7 x 35 cm)	
<b>Lid Depth</b>	<b>Bottom Depth</b>	<b>Total Depth</b>	
2.00" (5.1 cm)	11.80" (30 cm)	13.80" (35 cm)	
<b>Interior Cubic Volume</b>			
4.17 cubic feet (118.05 cubic decimeter)			
<b>Weight with foam</b>	<b>Weight without foam</b>	<b>Buoyancy Max.</b>	
29.5 lbs. (13.38 kg)	22.8 lbs. (10.34 kg)	332.77 lbs. (150.94 kg)	
<b>Range Temperature</b>	<b>No. of Wheels</b>	<b>Retractable Handle</b>	
-20 / 140° F (-29 / 60° C)	2	YES	

## **iM2975 Pelican Storm Case (Transport) Certificates**

• MIL-STD-810F • FED-STD-101C • ATA 300

## **iM2975 Pelican Storm Case (Transport) Accessories**

<b>Cat. #</b>	<b>Description</b>
<b>iM-LIDSTAY</b>	<b>Lid Stay</b>
<b>iM-VALVE-M-B</b>	<b>Manual Purge Valve</b>
<b>iM2975-DIV</b>	<b>Padded Dividers</b>
<b>iM2975-FOAM</b>	<b>8 pc. Replacement Foam Set</b>
<b>iM29XX-BEZEL</b>	<b>Base Bezel Kit</b>
<b>iM29XX-BEZEL-LID</b>	<b>Lid Bezel Kit</b>
<b>iM29XX-UTILITYORG</b>	<b>Utility Organizer</b>

### **Pelican Products, Inc.**

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [CSR.Consumer@pelican.com](mailto:CSR.Consumer@pelican.com) • [www.pelican.com](http://www.pelican.com)